

# AlgoSec 2000 Series Appliances

The AlgoSec 2000 Series appliances are designed to provide a smooth turnkey deployment of the AlgoSec Security Management Solution. Based on a hardened and optimized operating system, AlgoSec appliances deliver flexibility, scalability and extensibility to organizations of all sizes.

Model	2062	2162	2322
-------	------	------	------

## Specifications

Number of Supported Devices*	1 – 60	60 – 550	550 – 1,200
CPU	6 cores: Intel® Xeon® E5-2603 v3	16 cores: Intel® Xeon® E5-2600 v3	32 cores: Intel® Xeon® E5-2600 v3
Ram	16GB	64GB	128GB
LAN Port	2x 10/100/1000 Ethernet	4x 10/100/1000 Ethernet	4x 10/100/1000 Ethernet
Video Connection	VGA	VGA	VGA
USB	1 x USB 2.0 Ports 3 x USB 3.0 Ports	5 x USB 3.0 Ports	5 x USB 3.0 Ports
Power Supply	HP 550W FIO	HP 500W FS – Redundant	HP 800W FS – Redundant
Storage	2x 900GB	5x 900GB	8x 1200GB
iLO (Integrated lights out)	HP iLO Standard	HP iLO Standard	HP iLO Standard
Redundancy	SW RAID	HW RAID 5, Dual CPU Built-in fail-safe in case of a hard-drive failure	HW RAID 5, Dual CPU Built-in fail-safe in case of a hard-drive failure
Operating Temperature	10° to 35°C (50° to 95°F)	10°C to 35°C (50°F to 95°F)	10°C to 35°C (50°F to 95°F)
Operating Humidity	5% to 95%	8% to 90%	8% to 90%

## Physical Specifications

Form Factor	1U Rack form factor	1U Rack form factor	1U Rack form factor
Dimensions	H: 1.68" (4.32 cm) W: 17.11" (43.46 cm) L: 23.92" (60.76 cm)	H: 1.68" (4.32 cm) W: 17.11" (43.46 cm) L: 23.92" (60.76 cm)	H: 1.68" (4.32 cm) W: 17.11" (43.46 cm) L: 23.92" (60.76 cm)
Weight (maximum)	8 SFF 37.44 lb. (17kg)	8 SFF 33.3 lb. (15.31 kg)	8 SFF 33.3 lb. (15.31 kg)
Chassis	HP Rack Mount Consoles	HP Rack Mount Consoles	HP Rack Mount Consoles

## Compliance

### USA/Canada

FCC Part 15, Class A  
NFPA 70, 1999 Edition (National Electric Code), Article 250  
Canada CSA C22.1

### EMEA and International

International Electrotechnical Commission (IEC) Code 364, 1-7  
EMC: CISPR 22; EN55022; EN55024; FCC CFR 47, Pt 15; ICES-003; CNS13438; GB9254; K22; K24; EN 61000-3-2; EN 61000-3-3; EN 60950-1; IEC 60950-1

\* The number of firewalls supported by each appliance may vary according to policy complexity and the amount of logs collected. AlgoSec appliances can be deployed in a distributed architecture to scale to support environments of any size.

## Secure

- Hardened operating system optimized for the AlgoSec Security Management Solution

## Easy To Deploy

- Easy integration with your network
- Preloaded with the entire AlgoSec Security Management Solution

## Enterprise Grade

- Redundant components for maximum uptime
- High-availability using two appliances in active-standby mode
- Load-sharing between multiple appliances for increased scalability and fast report generation
- Geographically distributed architecture for improved network efficiency



### Global Headquarters

65 Challenger Road, Suite 320  
Ridgefield Park, NJ 07660  
USA  
+1-888-358-3696

### EMEA Headquarters

80 Coleman Street  
London EC2R 5 BJ  
United Kingdom  
+44-207-099-7545

### APAC Headquarters

10 Anson Road, #14-06  
International Plaza  
Singapore 079903  
+65-3158-2120

AlgoSec.com

